

REEL



EC Declaration of Conformity

Manufacturer: Reel EFX, Inc.

Responsible person to hold declaration of conformity, (established within EU)

Details of equipment:

Model Number(s): DF-50

Description: Smoke Machine

Directives this equipment complies with: EMC 89/336/EEC
LVD 73/23/EEC

Harmonized Standards applied in order to verify compliance with Directives: EN 50081-1
EN 50082-1

Year in which CE Mark was affixed: 1996

Authorized Signatory:

	Manufacturer	Date of Issue
Signature:		<u>1/1/15</u>
Name:	<u>Mark Ritner</u>	Place of Issue
Position:	<u>Sales Manager</u>	<u>California</u>

5539 RIVERTON AVE. ♦ N. HOLLYWOOD, CA. 91601
PHONE (818) 762-1710 ♦ FAX (818) 762-1734
Web Site: <http://www.reelefx.com>

MATERIAL SAFETY DATA SHEET (MSDS)

DIFFUSION FLUID FOR USE WITH REEL EFX DF-50

Identification of Any Dangers:

Inhaled: Acute exposure may result in bronchial irritation
Absorbed through skin: Chronic exposure may cause contact or eczematous dermatitis
Swallowed: May cause diarrhoea

Description of First Aid Treatment to be Given in Case of Emergency:

Eye Contact: Wash eyes with large amounts of water/saline solution occasionally lifting upper & lower eyelids until evidence of chemical is clear.
Skin Contact: Wash with soap & water.
Inhaled: Remove to fresh air.
Swallowed: No specific antidote. Treat symptomatically and supportively.

Fire Precautions:

Flash Point: Greater than 193 degrees Centigrade (closed cup)
Fire Extinguishing: Dry chemical, waterfog, CO₂, foam or sand/earth. Closed containers exposed to fire may be cooled with water.

Measures to be Taken in Case of Spillage:

Shut off leak and dyke up large spills. Absorb with an inert material such as sand, earth or vermiculite. Sweep up and dispose of in accordance with local regulations.

Precautions to be Taken in Storage & Handling:

Keep away from heat & flames. Do not store near strong oxidising agents such as hydrogen peroxide, bromide and chromic acid. The maximum storage temperature is 66 degrees Centigrade.

Precautions for Workers to Follow when Handling:

Respiratory Protection: Under normal use none.
When concentrations are above 5mg per cubic meter an approved air respirator.
Protective Clothing: Wear oil impervious clothing. Avoid wearing clothing soaked with mineral oil.
Wear appropriate protective gloves to avoid skin contact.
Always wear splash proof goggles when dealing with spills
Ventilation: Always ensure adequate ventilation to meet permissible

Precautions for Workers to Follow when Handling:

Respiratory Protection: Under normal use none.
When concentrations are above 5mg per cubic meter an approved air respirator.
Protective Clothing: Wear oil impervious clothing. Avoid wearing clothing soaked with mineral oil.
Wear appropriate protective gloves to avoid skin contact.
Always wear splash proof goggles when dealing with spills
Ventilation: Always ensure adequate ventilation to meet permissible exposure limits (PEL)

Stability & Reactivity:

Keep away from strong oxidisers such as hydrogen peroxide, bromide and chromic acid.

Toxicological Information:

Non toxic.

Ecological Information:

No data available. As the substance is not soluble in water do not flush into water or waste system.

Information Concerning Disposal of Waste Product:

Dispose of in accordance with all local regulations.

Information Concerning Transport of Product:

Department of Transport:	Non regulated.
Reportable Quantity:	None
Freight Classification:	65 Petroleum Oil
Special Transportation Notes:	None

Information Regarding Conformity to Relevant Regulations:

No data available for Europe.

The fluid meets the requirements of the US Food & Drug Administration
CFR 172.878

The fluid is not suspected to be a cancer agent.